



Premium 2 mil Foil Tape

Construction

Substrate : 2-mil Aluminum Foil

Adhesive: Solvent Acrylic

Liner: 60-lb Silicone Coated Kraft

Features:

An aggressive all-weather acrylic adhesive system

Bonds tightly and permanently to insulation facing & HVAC duct

Performs well over a wide range of environmental conditions

Foil backing provides a durable vapor barrier

UL Listed (File# R27953)

Eligible for LEED® compliance credits



Application

Application surface must be clean, dry and free of contaminants.

Apply pressure with plastic squeegee.

Shelf Life & Storage

Under ideal storage conditions of 60 F to 80 F and low humidity, shelf life is one year from date of purchase.

LEED®

US Green Building Council—LEED Green Building Rating System for New Construction and Major Renovations, v 2.2 Indoor Environmental Quality. Contributes towards EQ Credit 4.1 (Low Emitting Materials, Adhesives and Sealants). 1-Point. For more information on LEED and LEED submittals please visit www.usgbc.org/leed. Individual products are not LEED certified; LEED requirements consider material performance in aggregate.

Performance Data

Test	Typical Values (English)	Typical Values (metric)	Test Method
Total Thickness without Liner	0.0035-in	0.0889mm	PSTC-133
Peel Adhesion to Stainless Steel	70-oz/in	7.7-N/cm	PSTC-101
Tensile Strength	17-lbs/in	30-N/cm	PSTC-131
Elongation	3.5%	3.5%	PSTC-131
Permeance	0.0	0.0	ASTM E 96
Minimum Application Temperature	-25 F	-32 C	Mfg. Internal
Surface Burning Characteristics	0 Flame 0 Smoke	0 Flame 0 Smoke	UL 723 ASTM E 84

Availability/Packaging

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
2-in	150-ft	24	27
3-in	150-ft	16	27
4-in	150-ft	12	27



Performance values and characteristics shown are obtained through recommended test procedures. The listed values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from values indicated on the data sheet. User is responsible for determining suitability and fitness for use.



1650 Manheim Pike, Suite 202
Lancaster, Pa 17601-3088
Phone: (800) 788-7764
Fax: (717) 519-4046
Web: www.spi-co.com
www.winroc.com



Please ask your Sales Representative about our other products and services.